



MODEL 558/559

Hot-Water Pressure Washers

Powerful yet compact, these 115V gas-fired, hot-water pressure washers are great for stationary or portable applications.

2.2 GPM @ 1300 PSI

Model 558 (Propane) Model 559 (Natural Gas)



■ **Simple, easy-to-use control panel** includes adjustable temperature control plus heavy-duty heater and pump motor switches.

■ **2 HP, 115V, 1PH open drip-proof industrial motor** comes with thermal overload protection and manual reset.

■ **Safety pressure-relief valve** protects the machine and user.

■ **Upright, natural-draft burner** delivers high efficiency and maintains constant temperature using propane or natural gas.

■ **50-ft. high-pressure hose** for easy maneuverability around a large working area.

■ **Built-in wand holder** provides convenient storage.



Model 558 shown with optional portage kit. LP bottle not included with kit.

■ **Inlet water filter** protects pump from debris.

■ **37-ft. power cord** with safety **Ground Fault Circuit Interrupter (GFCI breaker)**.

■ **Adjustable, spray-angle nozzle** with 0° to 80° spray patterns adjusts easily under high pressure.



■ **Hot'sy duplex, direct-drive pump** carries seven-year crankcase and lifetime manifold warranties.

■ **Adjustable upstream detergent injection** ensures high-pressure sudsing for better cleaning.



■ **4 year, non-prorated heat exchanger warranty.**

Hotsy's Models 558 and 559 pack a powerful punch to defeat your toughest cleaning jobs.

Powerful, yet compact and versatile, Models 558 and 559 deliver exceptional cleaning performance by providing a steady stream of 2.2 GPM of hot water at 1300 PSI. Available in propane (Model 558) or natural gas (Model 559), these 115V machines are great for stationary or portable applications in commercial, agricultural, manufacturing and municipal applications.

Discover Hotsy's no-cost benefits

Choose the Model 558 or 559 for its high performance and reliability. Then enjoy the benefits of doing business with the leader in industrial cleaning equipment. You'll find more than 120 models of pressure washers to choose from, free on-site demos, factory-trained service people, pre-delivery dealer prep, on-site machine check-out, operator training, local parts and accessory inventory and an unbeatable warranty program.

Accessories to match your application

Hotsy's custom accessories tailor the Model 558 and 559 pressure washers to fit your specific requirements making your cleaning jobs faster, easier and more efficient. Choose from extra hose lengths, hose reels, wand extensions, quick couplers, downstream detergent injector, foam applicator, wet sand-blaster, rotating brush and more.



Clean better with Hotsy detergents

Hotsy's broad selection of biodegradable detergents are formulated specifically for high-temperature, high-pressure cleaning. This means you get the best results from your Hotsy pressure washer while continuously protecting the machine. Exclusive advanced-formula Hotsy Continuous Clean (HCC) additives continuously clean the lime and mineral buildup that can occur in your washer's coil and fittings. This cleaning action reduces replacement costs and improves machine performance. Most Hotsy detergents are USDA and Canadian Agriculture approved. And they're concentrated, so a little goes a long way.



Call today for a demo!

Find out for yourself why the Hotsy Models 558 and 559 are right for your cleaning jobs. Call your Hotsy distributor today for all the details and a FREE on-site demo.



Model 558/559 Specifications

2.2 GPM @ 1300 PSI; 2 HP, 115V, 1-phase electric motor; 20 Amp; gas-fired water heater; shipping weight: 310 lbs.

Water Pump Volume: 2.2 GPM (8.33 lpm); 132 GPH (499.8 lph).

Water Pump Pressure: 1300 PSI (89.66 bars).

Water Pump: Hawk® duplex, direct-drive, positive-displacement pump; ceramic plungers, brass manifold, oil-bath crankcase.

Pump Drive: 2 HP, 115V, 60 Hz, 1PH electric motor; 56 frame, open drip proof with thermal overload protection and manual reset.

Water Heater: Gas-fired; 245,000 BTU/hr. (propane) and 240,000 BTU/hr. (natural gas); AGA-listed gas controls, ring-type with aspirating spuds; natural draft; standing pilot. Your choice of propane fired (Model 558) vapor-type, (LP-gas tank required, but not included); or natural gas fired (Model 559).

Heating Coil: Schedule 80, ASTM A53 close coiling pipe; hydrostatic pressure tested; vertically fired. Heating coil is sheathed in a full-length sheet-metal wrap. Equipped with an independently welded heat-retention baffle plate.

Stack Size: 10" diameter.

Controls: Adjustable temperature control; self-cleaning, safety pressure-relief valve; heavy-duty rocker type on/off pump motor and water-heater switches; upstream detergent injector.

Wand Assembly: Trigger-gun control with cool grip, quick-coupled to heavy-duty, chrome-plated wand with insulated grip.

Nozzle: Adjustable, spray-angle nozzle with 0° to 80° spray patterns.

Hose: 3/8" ID, 50 ft. wire braid with swivel fittings at both ends; 3000 PSI working pressure; burst pressure is at least 4 times working pressure; oil and chemical resistant.

Portability: Optional

Optional Accessories: Draft diverter, portage kit, extra hose lengths, hose reels, wand extensions, quick couplers, downstream detergent injector, wet sand blaster, rotating brush and foam applicator.

Construction: Durable, heavy-gauge sheet-metal chassis.

Finish: High-gloss, powder coat.

Dimensions: L-28.50" (72.39 cm); W-20" (50.80 cm); H-31" (78.74 cm)



21 Inverness Way East, Englewood, Colorado 80112-5796 Tel: (303) 792-5200
1-800-525-1976 Fax: (303) 792-0547 e-mail: info@hotsy.com or visit our website: www.hotsy.com

P/N 97-0487 Printed in USA Effective 7/01 Specifications and product descriptions subject to change without notice. © 2001 Hotsy

America's #1 Manufacturer of Cleaning Systems

